



Stunner LED Strips

Product Manual

Visit us online at www.ecoxotic.com/support for installation videos on this and other Ecoxotic products.



Product Manual

Safety Instructions

To avoid injury and possible electric shock it is imperative that you
READ AND FOLLOW ALL SAFETY INSTRUCTIONS AND WARNINGS.

Important Warnings

This is NOT a page of legalese. It contains important safety information that you should read and save for future reference. Remember you can always quickly reference instructions for all EcoXotic products on our website.

- Always plug aquarium equipment into a GFCI (Ground To Fault Circuit Interrupter).
- Check for visible signs of water damage or salt deposits weekly and clean accordingly.
- Do not allow contact with water.
- Do not install near Metal Halide lamps or other light sources that are extremely hot.
- Do not install ballast in an area where it can get wet.
- Do not look directly into the LEDs.

Important Warnings: Drip Loops

Drip Loops should always be used to help prevent water from traveling along the cord and coming into contact with an electric outlet.

Drip loops must always be below the level of the outlet. If the plug or an outlet does get wet, DO NOT TOUCH the cord. Disconnect the fuse or circuit breaker that supplies power to the appliance. Then, unplug and examine for the presence of water.

Grounding Instructions

This appliance must be connected to a GFCI plug then to a grounded wall outlet to minimize the possibility of electric shock. This plug must be plugged into an outlet that is installed and grounded in accordance with all appropriate codes and ordinances.

This appliance is for use on a 120-volt circuit. If you do not have an available grounded outlet, you must have one installed by a qualified electrician.

SAVE THESE INSTRUCTIONS



Product Manual

Installation Instructions

What's in the box:

Stunner Strip with Adhesive Tape Backing
2 - 1/4" Screws
2 - Holding Clips
2 - Cord Clips

24V transformer
& 4-way splitter
sold separately

Tools you will need:

Phillips Screwdriver

There are three options for how to install your new Stunner Strip.

Option 1 – Adhesive Tape:*For applications that will not accept screws*

Use the 3M adhesive tape supplied on the back of the Stunner Strip. This tape is extremely aggressive and will stick to most surfaces. Simply clean the desired location. Remove the adhesive strip backing from the Stunner Strip and firmly place in the desired location.

Option 2 – Clips:*For applications where you wish to remove the strips periodically for cleaning*

Use the supplied clips, two per Stunner Strip. Simply screw the clips into the desired location in your canopy. Then, snap the Stunner Strips into place.

Option 3 – Screws:*For applications that accept screws, but will not need to be removed*

Place the Stunner in the desired location in your hood or canopy and attach it by placing the supplied screws through the ring attached on each end of the strip.

Once you have your new Stunner Strip installed in your hood or canopy, connect the male output of the power supply to the female connector on the Stunner. It is a simple water resistant snap fit. Use the supplied cord clips to support the cable as necessary.

Repeat the process for adding more than one Stunner Strip or use our 4-way splitter for connecting.

Finally, connect the output of the power supply to a Ground to Fault Circuit Interrupter (GFCI) and then into a 120V AC source.

Important Notes:

Go to www.ecoxotic.com/support to activate your warranty.

If you wish to use a timer to automate the lighting cycle for a dawn to dusk effect you must install a timer into the GFCI outlet in order for the GFCI to protect properly.

Always unplug the fixture when performing service on the aquarium or the Panorama LED Module.

